

XBO 1000 W/HTP OFR

XBO | Xenon short-arc lamps 450...10,000 W



Areas of application

- Classic 35 mm film projection
- Digital film and video projection
- Architectural and effect light ("Light Finger")
- Sunlight simulation

Product benefits

- Short arc with very high luminance for brighter screen illumination
- Constant color temperature of 6,000 K throughout the entire lamp lifetime
- Easy to maintain
- High arc stability
- Instant light on screen thanks to hot restart function
- Wide dimming range

Product features

- Color temperature: approx. 6,000 K (Daylight)
- Wattage: 1,200...8,000 W
- Very good color rendering index: R_a >








Product datasheet

Technical data

Electrical data

| Nominal wattage | 1000.00 W | |
|-----------------------|-----------|--|
| Lamp voltage | 21 V | |
| Nominal current | 45.0 A | |
| Lamp current | 45.0 A | |
| Current control range | 3055 A | |

Dimensions & weight



| Diameter | 46.0 mm |
|---|------------------------|
| Length | 330.0 mm |
| Length with base excl. base pins/connection | 277.00 mm |
| Light center length (LCL) | 123.0 mm ¹⁾ |
| Electrode gap cold | 4.8 mm |
| Product weight | 354.30 g |

 $^{^{1)}}$ Distance from end of base to tip of electrode (cold)

Temperatures & operating conditions

| Max. permitted ambient temp. pinch point | 230 °C |
|--|--------|

Lifespan

| Lifespan | 2400 h |
|----------|--------|
|----------|--------|

Additional product data

| Base anode (standard designation) | SFa25-14 |
|-------------------------------------|---|
| Base cathode (standard designation) | SFc25-14 |
| Product remark | OFR = Ozone-free version/H = Suitable for horizontal burning position/TP = Cable with threaded pins |

Product datasheet

Capabilities

| Cooling | Forced |
|------------------|-----------------------|
| Burning position | s30/p30 ¹⁾ |

 $^{^{}m 1)}$ For vertical burning position: anode (+) on top

Country specific information

| Product code | METEL code | SEG-No. | STK-Number | UK Org |
|---------------|------------------|---------|------------|--------|
| 4008321081353 | OSRXBO1000HTPOFR | - | - | - |

Product datasheet

Logistical Data

| Product code | Product description | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Volume | Gross weight |
|---------------|-----------------------|---------------------------------|--------------------------------------|-----------|--------------|
| 4008321081353 | XBO 1000 W/HTP OFR | Shipping carton box | 500 mm x 200 mm x 204 mm | 20.40 dm³ | 1223.33 g |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.